

# STORM SERIES

# YNS1100C SPECIFICATIONS 1100kVA





#### **GENERAL**

 Model
 YNS1100C

 Power Type
 Diesel

 Prime Power (kW/kVA)
 800/1000

 Standby Power (kW/kVA)
 880/1100

#### **ENGINE**

Engine Make and Model

Engine Type

Fuel Consumption (L/h)\*

Aspiration

Bore (mm) x Stroke (mm) No. of Cylinders

Displacement (L)
Compression Ratio

Governor Type

Lubricating Oil Capacity (L)

\*Fuel Consumption is based on 100% load

**CUMMINS KTA38.G5** 

Turbocharged, Aftercooled, 60 Vee, 12Cyl

209

Turbo-charged, Aftercooled

159 x 159

12 38

13.9:1

Electronic Governor

135.1

#### **ALTERNATOR**

Model	SLG404J
Frequency (Hz)	50
Rate Power (kW/kVA)	824/1030
Power Factor	0.8
Exciter Type	PMG
Voltage Regulator	AVR
Voltage Regulation	±0.5%
No. of Phases	3
Insulation	Class H
Protection	IP 21
Altitude (m)	1000

#### UNIT

Dimensions L x W x H (m) 5.8 x 2.25 x 2.58

 Dry Weight (kg)
 9000

 Sound at 7m/dB
 92

#### STANDARD FEATURES

- 50°C rated radiator
- Powder coated finish
- All moving parts fitted with safety guards
- Emergency E stop
- State of the art control system
- ATS available

#### **ASSEMBLY**

The engine and alternator are closed coupled by means of an SAE flange. A full torsional analysis has been carried out to guarantee no harmful vibration will occur. Anti-vibration pads are affixed between engine alternator feet and base frame. Rubber diagonal



isolators are specifically designed to reduce engine and alternator vibration and prevent distortion in the voltage and harmonic output of the generator. All iron and steel surfaces of the canopy fabrication have been sand blasted and then powder coated, which provides an excellent corrosion resistant surface.

# **CONTROL SYSTEM**

Automatic stop/start,
Data measurement, Alarm
protection and remote control,
remote measuring and remote
communication; SG485
module must be fitted in. LCD
display and it is easy and reliable to use.



## **QUALITY STANDARDS**

Our generator sets are compliant with all the main standards, such as ISO8528, ISO14000, GB755, BS5000, VDE0530, ISO3046, IEC34-1, AS3000.

## **WARRANTY POLICY**

12 months, 1200 hours as per generator. Generators Australia Pty Ltd Warranty Policy. All photos are for marketing purposes only.

Fuel Consumption is based on 100% load