

STORM SERIES

YNS16K SPECIFICATIONS

16kVA



Australian Design.
Powered by



GENERAL

Model	YNS16K
Power Type	Diesel
Prime Power (kW/kVA)	12/15
Standby Power (kW/kVA)	13/16

ENGINE

Engine Make and Model	KUBOTA D902-E3B-SAE-1
Engine Type	Vertical, Water-cooled, 4cycle IDI Diesel Engine
Engine Power (kW)	15/3000rpm
Fuel Consumption (L/h)*	2.3
Aspiration	Natural
Bore (mm) x Stroke (mm)	72 x 73.6
No. of Cylinders	3
Displacement (L)	0.898
Compression Ratio	23.5
Governor Type	All speed mechanical governor
Lubricating Oil Capacity (L)	3.8

*Fuel Consumption is based on 100% load

ALTERNATOR

Model	SLG182J
Frequency (Hz)	50
Rate Power (kW/kVA)	14/17.5
Power Factor	0.8
Exciter Type	Self-excited, brushless
Voltage Regulator	AS440
Voltage Regulation	+1.0%
No. of Phases	3
Insulation	Class H
Protection	IP 23
Altitude (m)	1000

UNIT

Dimensions L x W x H (m)	2.0 x 0.9 x 1.1
Dry Weight (kg)	750
Sound at 7m/dB	67

STANDARD FEATURES

- 50°C rated radiator
- Powder coated finish
- All moving parts fitted with safety guards
- Emergency E stop
- State of the art control system
- Outlets 1 x 3PH 32amp
- Outlets 2 x 1PH 15amp
- ATS available
- Single phase units available



ASSEMBLY

The engine and alternator are closed coupled by means of an SAE flange. A full torsional analysis has been carried out to guarantee no harmful vibration will occur. Anti-vibration pads are affixed between engine alternator feet and base frame. Rubber diagonal isolators are specifically designed to reduce engine and alternator vibration and prevent distortion in the voltage and harmonic output of the generator. All iron and steel surfaces of the canopy fabrication have been sand blasted and then powder coated, which provides an excellent corrosion resistant surface.



CONTROL SYSTEM

Automatic stop/start, Data measurement, Alarm protection and remote control, remote measuring and remote communication; SG485 module must be fitted in. LCD display and it is easy and reliable to use.



QUALITY STANDARDS

Our generator sets are compliant with all the main standards, such as ISO8528, ISO14000, GB755, BS5000, VDE0530, ISO3046, IEC34-1, AS3000.

WARRANTY POLICY

12 months, 1200 hours as per generator. Generators Australia Pty Ltd Warranty Policy. All photos are for marketing purposes only.