

# STORM SERIES

# **YNS412C SPECIFICATIONS 412KVA**





#### **GENERAL**

 Model
 YNS412C

 Power Type
 Diesel

 Prime Power (kW/kVA)
 300/375

 Standby Power (kW/kVA)
 330/412

#### **ENGINE**

Engine Make and Model

Engine Type

Fuel Consumption (L/h)\*

Aspiration

Bore (mm) x Stroke (mm) No. of Cylinders

Displacement (L)

Compression Ratio

Governor Type

Lubricating Oil Capacity (L)

\*Fuel Consumption is based on 100% load

**CUMMINS NTAA855-G7** 

Turbocharged, Air-cooled, In-line, 6cyl

85.4

Turbo-charged, Air to Air Cooled

140 x 152

14

14 0.1

Electronic Governor

38.6

#### **ALTERNATOR**

SI G314F1 Model Frequency (Hz) Rate Power (kW/kVA) 304/380 Power Factor Exciter Type Self-excited AS440 Voltage Regulator ±1.0% Voltage Regulation No. of Phases Insulation Class H Protection IP 21 Altitude (m) 1000

#### **UNIT**

 Dimensions L x W x H (m)
 4.2 x 1.5 x 2.3

 Dry Weight (kg)
 4800

 Sound at 7m/dB
 78

#### STANDARD FEATURES

- 50°C rated radiator
- Powder coated finish
- All moving parts fitted with safety guards
- Emergency E stop
- State of the art control system
- ATS available

### **ASSEMBLY**

The engine and alternator are closed coupled by means of an SAE flange. A full torsional analysis has been carried out to guarantee no harmful vibration will occur. Anti-vibration pads are affixed between engine alternator feet and base frame. Rubber diagonal



isolators are specifically designed to reduce engine and alternator vibration and prevent distortion in the voltage and harmonic output of the generator. All iron and steel surfaces of the canopy fabrication have been sand blasted and then powder coated, which provides an excellent corrosion resistant surface.

#### **CONTROL SYSTEM**

Automatic stop/start,
Data measurement, Alarm
protection and remote control,
remote measuring and remote
communication; SG485
module must be fitted in. LCD



display and it is easy and reliable to use.

## **QUALITY STANDARDS**

Our generator sets are compliant with all the main standards, such as ISO8528, ISO14000, GB755, BS5000, VDE0530, ISO3046, IEC34-1, AS3000.

#### **WARRANTY POLICY**

12 months, 1200 hours as per generator. Generators Australia Pty Ltd Warranty Policy. All photos are for marketing purposes only.