



## DIESEL LIGHTING TOWER



## GP6UrbanD

### GENERAL

Light Power	6 x 350W 48V DC
Lights	LED
Lumen Output	315,000
<b>GENSET</b>	
Generator	Kubota 1105
Fuel Type	Diesel
Fuel Consumption	1.1L/hr
Running Time	145 hours
Alternator	Sincro FB4-48/100, 48V DC
Noise Level	68dBA at 7m
Control System	Electronic genset control module with auto stop/start

### TRAILER

Wheels	16" x 6 Trac 2 rims
Tyres	235/R16 x 16"
Towing Speed (Max)	80km/hr
Fuel Tank Capacity	140L
Bunded	110%
Wind Speed Rating (Max)	100km/hr

### MAST

Mast Height (Max)	8.10m
Mast Type	Hydraulic
Mast Rotation	350° non-continuous
Mast Max Horizontal Outreach	3m
Mast Lift Time	110 seconds
Mast Lower Time	90 seconds
Telescope, Tilt	Hydraulic
Hydraulic System Pump	12V DC
Function Control	Electric over hydraulic
<b>UNIT</b>	

Dimensions (Stowed)	2400 x 2500 x 1750 mm
Dimensions (Deployed)	8100 x 3800 x 3170 mm
Weight	1600 kg

