



-  AUSTRALIAN
DESIGNED
-  FUEL EFFICIENT
-  CUSTOMISABLE
-  DURABLE

PRODUCT SPECIFICATIONS

GENERAL

Model	GP17FWS-1
Power Type	Diesel
Prime Power (kW/kVA)	12/12
Standby Power (kW/kVA)	13/13
Rated Current	50 AMPS
Operating Ambient Temp.	50°C

ENGINE

Engine Model	FAWE 4DW81-23D
Aspiration	Turbo-charged
No. of Cylinders	4
Governor Type	Electronic governor

ALTERNATOR

Model	SLG164D
Frequency	50
Rate Power (kW/kVA)	13/13
Power Factor	1
Exciter Type	Self-excited
Voltage Regulator	AVR
Voltage Regulation	±1.0%
No. of Phases	1
Insulation	Class H
Protection	IP21
Altitude	1000m

UNIT

Dimensions (LxWxH)	2000 x 1000 x 1290
Dry Weight	890kg

FUEL CONSUMPTION

Fuel Consumption*	4.95(L/h)
Fuel Tank Capacity	160L

NOISE LEVEL

Sound Pressure at 7m/dB	75
-------------------------	----

SAFETY FEATURES

ISO Compliant
Outlet package with AS3000 compliant RCD protection
Emergency E Stop

CONTROL SYSTEM

Operator friendly DSE6020 control system

ENCLOSURE FEATURES

Sound attenuated canopies
Powder coated finish
IP65 rating
Fully bunded extended run fuel tanks

WARRANTY

12 months warranty, subject to Ts & Cs

*Fuel consumption based on 75% load