







-  AUSTRALIAN DESIGNED
-  FUEL EFFICIENT
-  CUSTOMISABLE
-  DURABLE

## PRODUCT SPECIFICATIONS

### GENERAL

Model	GP17FWS-3
Power Type	Diesel
Prime Power (kW/kVA)	11/14
Standby Power (kW/kVA)	14/17
Rated Current	19 AMPS
Operating Ambient Temp.	50°C

### ENGINE

Engine Model	FAWE 4DW81-23D
Aspiration	Turbo-charged
No. of Cylinders	4
Governor Type	Electronic governor
Lubricating Oil Capacity	16.4L

### ALTERNATOR

Model	SLG164D
Frequency	50
Rate Power (kW/kVA)	12.8/16
Power Factor	0.8
Exciter Type	Self-excited
Voltage Regulator	AVR
Voltage Regulation	±1.0%
No. of Phases	3
Insulation	Class H
Protection	IP21
Altitude	1000m

### UNIT

Dimensions (LxWxH)	2240 x 950 x 1620
Dry Weight	890kg

### FUEL CONSUMPTION

Fuel Consumption*	4.95(L/h)
Fuel Tank Capacity	160L

### NOISE LEVEL

Sound Pressure at 7m/dB 75

### SAFETY FEATURES

ISO Compliant  
 Outlet package with AS3000 compliant RCD protection  
 Emergency E Stop  
 Fitted with ATS

### CONTROL SYSTEM

Operator friendly DSE6020 control system

### ENCLOSURE FEATURES

Sound attenuated canopies  
 Powder coated finish  
 IP65 rating  
 Fully bunded extended run fuel tanks

### WARRANTY

12 months warranty, subject to Ts & Cs

\*Fuel consumption based on 75% load

GP-GP17FWS-3-V3-0726